



XRT 1550 (GAS)

AS CONFIGURED

\$15,511

Prices valid for US only. Outside US: Different prices, duties, and taxes may apply. Excludes freight, Set up, Manufacturer Surcharge, and Tax

QUOTED :

SPECIFICATION :

ENGINE Kawasaki 4-Cycle, Industrial Grade
 DISPLACEMENT 675 Cc
 CYLINDERS Twin
 VALVING Overhead Valve
 COOLING Air Cooled
 HORSEPOWER 20.1 Hp (15.0 KW) Rated @ 3400 RPM Per SAE J1349
 MAX TORQUE 36.5 Ft-Lb (49.5 N-M)
 LUBRICATION / OIL FILTER Pressure Lubrication; Spin-On Oil Filter
 GOVERNOR Automatic Ground Speed Sensing
 FUEL DELIVERY SYSTEM Carburetor
 FUEL CAPACITY 6.5 Gal (24.6 L)
 TRANSMISSION Continuously Variable Transmission (CVT) With IntelliTrak Automatic 4-Wheel Drive
 GEAR SELECTION Forward/Neutral/Reverse
 GEAR RATIO 5.39:1 Forward; 7.79:1 Reverse; 3.3:1 Differential
 IGNITION Transistorized Magneto
 BATTERY 12-Volt 500 CCA; 105 Min Reserve Capacity
 HEADLIGHTS Two 55 Watt Halogen
 STEERING Self-Adjusting Rack And Pinion With Adjustable Tilt
 SUSPENSION (FRONT) Independent Double A-Arms With Coil-Over Shocks
 SUSPENSION (REAR) Semi-Independent 4-Link Suspension With Coil Over Shocks
 BRAKES Twin Piston, Hydraulic Disc (Front); Single Piston, Hydraulic Disc (Rear)
 PARK BRAKE Foot-Pedal Activated, Mechanical Disc
 TIRES (FRONT) 25 X 10.5-12, 6-Ply Rated, Mud Tire
 TIRES (REAR) 25 X 10.5-12, 6-Ply Rated, Mud Tire
 BODY (FRONT & FINISH) GE Gelyo High-Impact, Scratch-Resistant, Injection Molded Color With Automotive Finish
 BODY (REAR) Molded Plastic Over Aluminum Frame
 WHEELBASE 81.5 In (207 Cm)
 OVERALL HEIGHT 82.3 In (209 Cm)
 OVERALL LENGTH 122 In (309.9 Cm)
 MAX WIDTH (W/O MIRRORS) 58.5 In (148.5 Cm)
 GROUND CLEARANCE 8.2 In (21.0 Cm)
 TRACK WIDTH (FRONT) 48.8 In (124 Cm)
 TRACK WIDTH (REAR) 48.8 In (124 Cm)
 CARGO BED LxWxH 48.0 X 49.8 X 10.9 In (122 X 127 X 28 Cm)
 VEHICLE CURB WEIGHT 1,430 Lb (649 Kg)
 BED LOAD CAPACITY 800 Lb (363 Kg) - Standard; 1050 Lb (476 Kg) W/ HD Suspension
 TOTAL VEHICLE CAPACITY 1,200 Lb (544 Kg) - Standard; 1,450 Lbs (658 Kg) With HD Suspension
 TOWING CAPACITY 2,000 Lb (907.2 Kg)
 COMBINATION RATED CAPACITY 2,500 Lb (1,134 Kg) - Standard; 2,750 Lb (1,247.4 Kg) With HD Suspension
 SPEED 25 Mph (40.2 Kph)
 WARRANTY - POWERTRAIN 2 Year Limited Powertrain And Frame Warranty
 WARRANTY - VEHICLE 1 Year Limited Remaining Vehicle

* Vehicles specifications apply to the base model and may not reflect all selected options or accessories.



OPTIONS

Exterior Color :
 Red Front Panels

Seating :
 Gray Bench Seat

Powertrain :
 Gas

Tire & Wheels :
 25" Mud Tires On Black Steel Wheels

Canopy :
 No Canopy

Windshield :
 No Windshield

Cab :
 No Cab

Bumper/Guard Protection :
 Tube Bumper* \$141

Lighting Options :
 No Lighting Options

Enclosures :
 No Enclosures

Finance rates are estimates only and are subject to change without notice. Actual rate may vary.

All loans are subject to credit review and approval. Please contact your local Club Car dealer for more information.